



Electrical Specifications

Voltage: 24 VDC
Duty Cycle: 10%
Resistance: 17.5 ohms \pm 10% (@ 20c)
Amps @ rated Volts: 1.37
Watts @ rated Volts: 32.91
Holding: 215 lbs (1/4" Thick 1215 CRS @ 20c)
Operating Temp: -40c to 60c (range)
Lead Wire Positive: Red
Lead Wire Negative: Brown

| UNLESS OTHERWISE SPECIFIED: | | NAME | DATE | APW COMPANY | |
|---|-----------|------|---------|--------------|--------------|
| DIMENSIONS ARE IN MM | DRAWN | DP | 9.27.23 | TITLE: | |
| TWO PLACE DECIMAL \pm .25 | CHECKED | | | EML63mm-24 | |
| THREE PLACE DECIMAL \pm .13 | ENG APPR. | | | SIZE | DWG. NO. |
| | MFG APPR. | | | A | 6682 |
| Break Sharp edges 0.05 unless otherwise noted | Q.A. | | | SCALE: 1:1.5 | WEIGHT: |
| MATERIAL | COMMENTS: | | | | SHEET 1 OF 1 |
| FINISH | | | | | |
| DO NOT SCALE DRAWING | | | | | |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.